xerox™

Xerox® C325 Color Multifunction Printer

Work doesn't slow down, and your printer shouldn't either.



SYSTEM SPECIFICATION	XEROX C325 COLOR MULTIFUNCTION PRINTER	
PRINT SPEED (UP TO:)		
One-sided Speed¹ – Letter/A4 Color, Black-and-White	35/33 ppm	
Two-sided Speed¹ – Letter/A4 Color, Black-and-White	17.5/17 ipm	
Monthly Duty Cycle ² (Up To:) Pages Per Month	65,000	
Recommended Average Monthly Print Volume (Up To:) Pages Per Month	6,000	
Processor/Memory Clock Speed/Cores Memory	1.2 GHz Quad Core Processor 2GB RAM, 8GB eMMC	
Connectivity Device Connectivity	Hi-Speed USB 2.0 (Type A port 1 front, 1 rear), Hi-Speed USB (Type B port 1 rear), Gigabit Ethernet, Wireless 802.11 b/g/n	
Imaging Technology	Color Laser	
PRINT AND COPY		
Print Resolution (Up To:)	1200 x 1200 dpi, 4800 Color Quality	
Copy Resolution (Up To:)	600 x 600 dpi	
First-print-out Time (As Fast As:)	7.5 seconds color/7.2 seconds B&W	
First-copy-out Time (As Fast As:)	7.1 seconds color/6.8 seconds B&W	
Page Description Languages	PostScript® 3 Emulation, PCL® 6 Emulation, PCL 5, XPS, PDF v1.7 Emulation, HTML, Direct Image	
Print Features	One Touch UI, Print Quality, Normal, Secure, Saved, and Sample Set Job Types, Duplex, Orientation, Collation, Print Job ID in Margins, Draft Mode, N-up, Booklet Layout, Watermark, Tray and Toner Status, Rotate Image 180 Degrees, Saved Settings, Earth Smart Settings	

SYSTEM SPECIFICATION	XEROX C325 COLOR MULTIFUNCTION PRINTER	
MOBILE- AND CLOUD-READY		
Mobile Printing	Apple AirPrint, Mopria Print Service, Chromebook, Wi-Fi Direct®	
Mobile Scanning	Apple AirPrint, Mopria Scan Service	
Xerox® Workplace Suite and Xerox® Workplace Cloud	Yes	
Cloud Connectivity	Yes (Via the Xerox® Print and Scan Experience App)	
SCAN		
Destinations	Email, Front-side USB drive, FTP, Network or USB Connected Computer, Windows Network Folder	
File Formats	TIFF, JPEG, PDF (OCR available through Xerox® Print and Scan Experience App for Windows), Secure PDF, XPS	
FAX		
Standard Features	MH/MR/MMR/JBIG/JBIG2/JPEG Compression, Auto Answer, Auto Redial, Auto Reduction, Broadcast Send, Junk Fax Filter, Fax Address Book, Fax Forward, which includes: Fax, Email, FTP, Network Folder, Called Number	
PRINT DETAILS		
First-print-out Time – Color (As Fast As:)	7.5 seconds	
First-print-out Time – B&W (As Fast As:)	7.2 seconds	
Resolution (Up To:)	1200 x 1200 dpi, 4800 Color Quality	
Page Description Languages	PostScript® 3 Emulation, PCL® 6 Emulation, PCL 5, XPS, PDF v1.7 Emulation, HTML, Direct Image	
Unprintable Page Margin	Print: 4.2 mm from each edge; Copy: 3 mm from each edge	
Print from USB	File Formats: Microsoft Office Formats (Word, Excel, PPT), PDF, HTML, XPS, Image Formats (JPEG, TIFF, GIF, BMP, PNG, PCX) Options available to configure prints from USB: paper source, print blank pages, collate, two-sided printing, paper saver orientation, separator sheets paper saver, paper saver ordering	
Print Driver Types/Operating Systems	Windows® 11, Windows® 10, Windows Server 2022, Windows Server 2019, Windows Server 2012 R2, Windows Server 2012. macOS 13.x, macOS 12.x, macOS 11.x. Microsoft Universal Print with Print Support Application. For the latest information about supported Operating Systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com .	
Network Protocols	TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, Raw Socket Printing/Port 9100, IPv4/IPv6, MS Web Services WSD-Print, 802.1x, SNMP, ThinPrint, Microsoft Universal Print, Bonjour	
Font Capability	PCL6 94 Scalable Fonts, 2 Bitmapped PS Emulation, 163 Scalable Fonts	
COPY DETAILS		
First-copy-out Time – Color (As Fast As:)	7.1 seconds	
First-copy-out Time – B&W (As Fast As:)	6.8 seconds	
Simplex Speed (Up To:)	35 ppm/33 ppm Letter/A4	
Duplex Speed (Up To:)	17 ipm Letter/17 ipm A4	
Sides (Input:Output)	1:1, 1:2, 2:1, 2:2	
Quantity	1-9,999	
Concurrency	Yes (Copy while printing)	
Copy Features	Copy From Size; Copy To Size; Scale 25% to 400%; Darkness/Lightness; Sides 1:1, 1:2, 2:1, 2:2; Duplex; Collate; Sample Copy; Content Type – Text, Text/Photo, Photo, Graphics; Content Source – B&W Laser, Color Laser, Inkjet, Photo/Film, Magazine, Newspaper, Press, Other; Create Shortcut; Color Advanced Options Paper Setup; Advanced Imaging, Auto Centre, Background Removal, Contrast, Mirror Image, Negative Image, Scan Edge to Edge, Shadow Detail, Sharpness, Color Balance, Color Dropout; Create Booklet; Cover Page Setup; Custom Job Build; Edge Erase; Header/Footer; Margin Shift; Overlay; Pages per Side – 2 pages per side, 4 pages per side; Separator Sheets – Between Pages, Between Copies, Between Jobs	

SYSTEM SPECIFICATION	XEROX C325 COLOR MULTIFUNCTION PRINTER		
SCAN DETAILS			
Technology	Color Flatbed Scanner with Single-pass DADF, Contact Image Sensor (CIS)		
Capability	Single-pass DADF, up to 50 sheets of 75 gsm, Color/B&W		
Concurrency	Yes (Scan while printing)		
Input Speed – Color (Up To:)	30/28 ipm Simplex Letter/A4, 40/38 ipm Duplex Letter/A4		
Input Speed – B&W (Up To:)	40/38 ipm Simplex Letter/A4, 50/47 ipm Duplex Letter/A4		
Resolution	600 x 600 dpi		
Resolution (Software Utilities) (dpi)	150 x 150, 200 x 200, 300 x 300, 400 x 400, 600 x 600		
Maximum Scan Area (ADF) (in)	8.5 x 14 in		
Maximum Scan Area (ADF) (mm)	216 x 356 mm		
Maximum Scan Area (Platen) (in)	8.5 x 14 in		
Maximum Scan Area (Platen) (mm)	216 x 356 mm		
Media Weight (ADF)	52 to 120 gsm		
Network Filing Protocol	FTP, SFTP, SMB, USB, Windows Network Folder		
File Formats	TIFF, JPEG, PDF (OCR available through Xerox® Print and Scan Experience App for Windows), XPS		
Scan Driver Compatibility	TWAIN, WIA, ICA		
Scan File Compression Options	PDF – 1 bit – JBIG2, CCIT G4, Flate 8/24 bit – Flate, JPEG TIFF – 1 bit – CCITT G4 8/24 bit – Packbits, LZW JPG – 8/24 bit – JPEG		
Supported Scan Destinations	Email, Front-side USB Drive, FTP, LDSS, Network or USB Connected Computer, Windows Network Folder		
FAX DETAILS			
Fax Speed	33.6 Kbps		
Memory	18 MB		
Resolution (dpi)	B&W standard 200 x 100 send, 200 x 100, 204 x 98 receive B&W fine 200 x 200 send, 200 x 200, 204 x 196 receive B&W superfine 300 x 300 send, 300 x 300, 204 x 391 receive B&W ultrafine 600 x 600 send, 600 x 600, 400 x 400, 408 x 391 receive Color fine 200 x 200 send, 200 x 200 receive Color superfine 300 x 300 send, 300 x 300, 400 x 400 receive		
Fax Features	Auto Answer, Auto Redial, Auto Reduction, Broadcast Send, Junk Fax Filter, Fax Address Book		
Fax Forward Destinations	Fax, E-mail, FTP, Network Folder, Called Number		
DEVICE MANAGEMENT			
Device Management	Xerox® Easy Assist App, Remote Operator Panel, Xerox® Embedded Web Server		
Xerox® CentreWare® Web Software	Yes		
ACCESSIBILITY			
Accessibility	Voice Guidance available with ability to reduce background noise via headphones inserted in headphone jack		
SECURITY			
Security Protocols/Features	Digitally Signed Firmware Updates, Trusted Platform Module (TPM 2.0), WPA3, TLS 1.3, FIPS 140-2, Certificate Management, Secure Password Reset, TCP Connection Filtering, Port Filtering, Access Controls, Confidential Print, Non-volatile Memory Wipe, Fax/Network Separation, Protected USB Ports, Auto Insertion of Sender's Email Address, Login Restrictions, Audit Log, Syslog		
WI-FI SECURITY			
Authentication and Encryption Methods	802.11 b/g/n/ac, Infrastructure (BSS) Mode, WEP Encryption (64 & 128-bit keys), WPA2/WPA Personal AES PSK, WPA2-Personal, WPA3 Support 802.1x; EAP-MD5, EAP-MSCHAPv2, EAP-TLS, EAP-TLS (CHAPS/IMSCHASPv2/PAP), LEAP, PEAP		

SYSTEM SPECIFICATION	XEROX C325 COLOR MULTIFUNCTION PRINTER
PAPER HANDLING	
SINGLE-PASS DUPLEX AUTOR	MATIC DOCUMENT FEEDER (DADF)
Type of ADF	Single-pass Duplex Automatic Document Feeder (DADF)
Capacity (Up To:)	50 sheets of 75 gsm stock; capacities will vary with different weight stocks
Minimum Mediα Size (in)	4.1 x 5.8 in
Minimum Media Size (mm)	105 x 148 mm
Maximum Media Size (in)	8.5 x 14 in
Maximum Media Size (mm)	216 x 356 mm
Minimum to Maximum Media Weight	52 to 120 gsm
PLATEN	
Maximum Media Size (in)	8.5 x 14 in
Maximum Media Size (mm)	216 x 356 mm
MANUAL FEED SLOT	
Standard/Optional	Standard
Capacity ³	1 sheet of 75 gsm
Minimum Mediα Size (in)	3 x 5 in
Minimum Mediα Size (mm)	76 x 127 mm
Maximum Media Size (in)	8.5 x 14 in
Maximum Media Size (mm)	216 x 356 mm
Minimum to Maximum Media Weight	60 gsm to 216 gsm (simplex)/60 gsm to 105 gsm (duplex)
Media Types Supported	Light Paper, Plain Paper, Heavy Paper, Cardstock, Envelopes, Labels
MAIN TRAY	
Standard/Optional	Standard
Capacity (Up To:) ³	250 sheets of 75 gsm
Minimum Media Size (in)	3.9 x 5.8 in
Minimum Mediα Size (mm)	98 x 148 mm
Maximum Media Size (in)	8.5 x 14 in
Maximum Media Size (mm)	216 x 356 mm
Minimum to Maximum Media Weight	60 gsm to 216 gsm (simplex)/60 gsm to 105 gsm (duplex)
Media Types Supported	Light Paper, Plain Paper, Heavy Paper, Labels, Cardstock, Envelopes

SYSTEM SPECIFICATION	XEROX C325 COLOR MULTIFUNCTION PRINTER		
PAPER HANDLING (CONTINU	PAPER HANDLING (CONTINUED)		
OPTIONAL 550+100-SHEET T	OPTIONAL 550+100-SHEET TRAY (INCLUDES 550-SHEETS STANDARD CAPACITY AND ADDITIONAL 100-SHEET BYPASS TRAY)		
550+100-SHEET TRAY - 100-SHEET BYPASS TRAY			
Standard/Optional	Optional – included with the 550+100-sheet Tray		
Capacity (Up To:) ³	100 sheets of 75 gsm		
Minimum Mediα Size (in)	3 x 5 in		
Minimum Mediα Size (mm)	76 x 127 mm		
Maximum Media Size (in)	8.5 x 14 in		
Maximum Media Size (mm)	216 x 356 mm		
Minimum to Maximum Media Weight	60 gsm to 176 gsm (simplex)/60 gsm to 105 gsm (duplex)		
Media Types Supported	Light Paper, Plain Paper, Heavy Paper, Labels, Cardstock, Envelopes		
550+100-SHEET TRAY - 550-	SHEET TRAY		
Standard/Optional	Optional – included with the 550+100-sheet Tray		
Capacity (Up To:) ³	550 sheets of 75 gsm		
Minimum Mediα Size (in)	5.8 x 8.3 in		
Minimum Mediα Size (mm)	148 x 210 mm		
Maximum Media Size (in)	8.5 x 14 in		
Maximum Media Size (mm)	216 x 356 mm		
Minimum to Maximum Media Weight	60 gsm to 176 gsm (simplex)/60 gsm to 105 gsm (duplex)		
Media Types Supported	Light Paper, Plain Paper, Heavy Paper, Labels, Cardstock		
STANDARD/MAXIMUM INPU	T CAPACITY		
Standard Input Capacity ³	251		
Maximum Input Capacity ³	901		
OUTPUT CAPACITY			
Output Capacity	200		

SYSTEM SPECIFICATION	XEROX C325 COLOR MULTIFUNCTION PRINTER	
DEVICE SPECIFICATIONS		
ELECTRICAL REQUIREMENTS		
North America	Voltage: 110–127 VAC +/-10% Frequency: 57/63Hz +/- 3 %, 10A	
Europe	Voltage: 220–240 VAC +/-10% Frequency: 57/63Hz +/- 3%, 5A	
POWER CONSUMPTION		
Running (Average)	Simplex: 574W; Duplex: 383W	
Typical Electricity Consumption (kWh)	0.51	
Standby Mode	25.5W	
Sleep Mode	1.3W (Default time to sleep mode = 15 minute)	
Warm Up From Hibernate	65 seconds	
OPERATING ENVIRONMENT		
Required Temperature Range	50 to 90°F/10 to 32.2°C	
Required Relative Humidity	15 to 80% RH	
Sound Power Levels Operating	6.9 B(A) or less	
Standby	3.1 B(A) or less	
Sound Pressure Levels Operating	54 db(A) or less	
Standby	14 db(A) or less	
DIMENSIONS AND WEIGHTS		
C325 Engine (Unpackaged)	Width: 18.9 in/479 mm Depth: 18.7 in/475 mm Height: 19.3 in/491 mm Weight: 59.5 lb/27.1 kg	
550+100-Sheet Tray (Unpackaged)	Width: 16.7 in/424 mm Depth: 16.4 in/416 mm Height: 5.2 in/133 mm Weight: 9.3 lb/4.2 kg	
Printer Stand (Unpackaged)	Width: 18.2 in/463 mm Depth: 20 in/510 mm Height: 17.3 in/440 mm Weight: 32.7 lb/14.8 kg	
C325 Engine (Packaged)	Width: 22.6 in/575 mm Depth: 25.0 in/636 mm Height: 23.6 in/600 mm Weight: 71.0 lb/32.3 kg	
550+100-Sheet Tray (Packaged)	Width: 8.6 in/218 mm Depth: 20.0 in/508 mm Height: 18.8 in/478 mm Weight: 11.45 lb/5.2 kg	
Printer Stand (Packaged)	Width: 20.7 in/525 mm Depth: 22.2 in/565 mm Height: 9.2 in/235 mm Weight: 37.7 lb/17.1 kg	
INSTALLATION CONSIDERATIONS		
Clear area around the device is necessary for access and ventilation. The table below shows the area needed on each side for correct installation.		
Тор	31.3 in/79.6 cm	
Rear	4 in/10.2 cm	
Left	3 in/7.2 cm	
Right	12 in/30.5 cm	
Front	20 in/50.8 cm	

SYSTEM CERTIFICATION/REGULATORY COMPLIANCE			
Certifications	To view the latest list of certifications, go to xerox.com/OfficeCertification	ns	
WHAT'S IN THE BOX			
All items contαined in the box	C325 Color Multifunction Printer Power Cord Installation Guide Product Safety Sheet Quick Use Guide Software and Documentation CD One of each (Cyan, Magenta, Yellow) 1,000 print capacity ⁴ ; Black cartridge: 1,500 print capacity ⁴		
SUDDITES AND ACCESSORIE		NORTH AMERICA	ALL OTHER REGIONS

SUPPLIES AND ACCESSORIES	NORTH AMERICA AND EUROPE*	ALL OTHER REGIONS
Genuine Xerox Black Standard Capacity Toner Cartridge, Xerox® C325 Color Multifunction Printer (2,200 Pages) ⁴	006R04823	006R04827
Genuine Xerox Cyan Standard Capacity Toner Cartridge, Xerox® C325 Color Multifunction Printer (1,800 Pages) ⁴	006R04820	006R04824
Genuine Xerox Magenta Standard Capacity Toner Cartridge, Xerox® C325 Color Multifunction Printer (1,800 Pages) ⁴	006R04821	006R04825
Genuine Xerox Yellow Standard Capacity Toner Cartridge, Xerox® C325 Color Multifunction Printer (1,800 Pages) ⁴	006R04822	006R04826
Genuine Xerox Black High Capacity Toner Cartridge, Xerox® C325 Color Multifunction Printer (8,000 Pages) ⁴	006R04831	006R04835
Genuine Xerox Cyan High Capacity Toner Cartridge, Xerox® C325 Color Multifunction Printer (5,500 Pages) ⁴	006R04828	006R04832
Genuine Xerox Magenta High Capacity Toner Cartridge, Xerox® C325 Color Multifunction Printer (5,500 Pages) ⁴	006R04829	006R04833
Genuine Xerox Yellow High Capacity Toner Cartridge, Xerox® C325 Color Multifunction Printer (5,500 Pages) ⁴	006R04830	006R04834
Genuine Xerox Waste Toner Bottle, Xerox® C325 Color Multifunction Printer (30,000 Pages) ⁵	008R13325	008R13325
Genuine Xerox Black Imaging Kit, Xerox® C325 Color Multifunction Printer (125,000 Pages) ⁶	013R00700	013R00700
Genuine Xerox Black and Color Imaging Kit (CMYK), Xerox® C325 Color/Multifunction Printer (125,000 Pages) ⁶	013R00701	013R00701
OPTIONAL ACCESSORIES		
550+100-Sheet Tray	097N02468	
Printer Stand	097S05244	

^{*} North America (NA): USA, Canada

Europe (KE): UK, France, Germany, Spain, Italy, Netherlands, Belgium, Norway, Sweden, Finland, Denmark, Iceland, Luxembourg, Austria, Switzerland, Portugal, Ireland, Andorra, Azores, Corsica, Greenland, Iceland, Lichtenstein, Luxembourg, Madeira, San Marino

For more information, visit us at www.xerox.com/en-us/office.



Declared print speed in accordance with ISO/IEC 24734.
 Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
 Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.
 Average standard pages. Declared yield in accordance with ISO/IEC 19798. Yield will vary based on image and area coverage.

SWaste Toner Container yield will vary depending on the type of image, area coverage %, and job run length.
Average drum yield is based on a run length of 5 pages of 8.5 x 11 in/A4 LEF pages, with a split of 35% color/65% black-and-white pages.