

# Xerox® VersaLink® B615 Multifunction Printer

VersaLink® B615 Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to [www.ConnectKey.com](http://www.ConnectKey.com).



SYSTEM SPECIFICATIONS	VERSALINK® B615
<b>One-sided Speed<sup>1</sup></b> 8.5 x 11 in. A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm	Up to 65 ppm black-and-white Up to 63 ppm black-and-white Up to 54 ppm black-and-white
<b>Two-sided Speed<sup>1</sup></b> 8.5 x 11 in. A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm	Up to 58.5 ppm black-and-white Up to 56 ppm black-and-white Up to 30.1 ppm black-and-white
<b>Monthly Duty Cycle<sup>2</sup></b>	Up to 300,000 pages/month
<b>Recommended Average Monthly Print Volume<sup>3</sup></b>	Up to 30,000 pages
<b>Hard Drive</b>	320 GB HDD
<b>Processor</b>	1.05 GHz ARM Dual Core
<b>Memory</b>	2 GB
<b>Connectivity</b>	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair
<b>Controller Features</b>	Unified Address Book, Configuration Cloning, Scan Preview, Xerox Extensible Interface Platform®, Xerox® App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support
<b>User Interface Languages</b>	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian

# Xerox® VersaLink® B615 Multifunction Printer

DEVICE SPECIFICATIONS				
ELECTRICAL REQUIREMENTS				
North America	Voltage: 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3% Hz, 12 A			
Europe and Other Geographies	Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 3% Hz, 8 A			
POWER CONSUMPTION				
Continuous Print <sup>4</sup>	950 watts or less			
Ready (Standby) <sup>4</sup>	79 watts or less			
Energy Saver (Sleep Mode) <sup>4</sup>	0.88 watts or less			
Power Off Mode <sup>4</sup>	220-240 VAC: 0.3 watts or less 110-127 VAC: 0.2 watts or less			
OPERATING ENVIRONMENT				
Required Temperature Range (Storage)	32° to 95° F/0° to 35° C			
Required Temperature Range (Operating)	50 to 90° F/10 to 32° C			
Required Relative Humidity	15% to 85%			
Sound Power Levels Running Standby	70 dB(A) or less 43 dB(A) or less			
Sound Pressure Levels Running Standby	58.3 dB(A) or less 29 dB(A) or less			
Boot Time (from Off to UI Ready)	Less than 79 seconds			
Warm-up Time (from Sleep to UI Ready)	Less than 47 seconds			
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
Base Unit (Short)	18.5 in./470 mm	19.8 in./502.8 mm	25.3 in./643.7 mm	67.2 lb./30.5 kg
Base Unit (Tall)	18.5 in./470 mm	19.8 in./502.8 mm	33.3 in./843.7 mm	71.7 lb./32.5 kg
Base Unit with Finisher	18.5 in./470 mm	19.8 in./502.8 mm	33.3 in./843.7 mm	86.7 lbs./39.3 kg
Base Unit with Mailbox	18.5 in./470 mm	19.8 in./502.8 mm	33.3 in./843.7 mm	83.4 lbs./37.8 kg
Base Unit with High Capacity Feeder and Finisher	18.5 in./470 mm	19.8 in./502.8 mm	56.1 in./1425.7mm	144.6 lbs./65.6 kg
Base Unit with High Capacity Feeder and Mailbox	18.5 in./470 mm	19.8 in./502.8 mm	56.1 in./1425.7mm	141.3 lbs./64 kg
550-sheet Tray	16.5 in./420 mm	10.4 in./464.5 mm	4.8 in./123 mm	14.6 lb./6.6 kg
High Capacity Feeder (includes Caster Base)	28.5 in./724.2 mm	30.4 in./772.1 mm	18 in./459 mm	43.3 lb./19.7 kg
Cabinet (includes Caster Base)	28.5 in./724.2 mm	30.4 in./772.1 mm	13.2 in./336 mm	37 lb./16.6 kg
Caster Base	28.5 in./724.2 mm	30.4 in./772.1 mm	3.5 in./90 mm	18.7 lb./8.5 kg
Mailbox	17.7 in./450.8 mm	18.8 in./477.6 mm	9.8 in./248.0 mm	11.7 lb./5.3 kg
Finisher	17.7 in./450.8 mm	16.2 in./411.0 mm	9.8 in./248.0 mm	15 lb./6.8 kg

# Xerox® VersaLink® B615 Multifunction Printer

<b>DIMENSIONS AND WEIGHT (PACKAGED)</b>	<b>WIDTH</b>	<b>DEPTH</b>	<b>HEIGHT</b>	<b>WEIGHT</b>
<b>Base Unit (Short)</b>	23.4 in/594 mm	25.8 in/655 mm	31.1 in/789 mm	83.8 lb./38 kg
<b>Base Unit (Tall)</b>	23.4 in/594 mm	25.8 in/655 mm	39.2 in/996 mm	94.8 lb./43 kg
<b>550-sheet Tray</b>	21 in/535 mm	23 in/584 mm	9.8 in/248 mm	18.7 lb./8.5 kg
<b>High Capacity Feeder</b>	22.4 in/568 mm	26.1 in/663 mm	28 in/711 mm	79.4 lb./38 kg
<b>High Capacity Feeder (includes Caster Base)</b>	22.4 in/568 mm	26.1 in/663 mm	28 in/711 mm	79.4 lb./38 kg
<b>Cabinet (includes Caster Base)</b>	23 in/584 mm	24.8 in/629 mm	23.5 in/597 mm	57.3 lb./28 kg
<b>Caster Base</b>	23 in/585 mm	24.4 in/619 mm	13 in/330 mm	39.7 lb./18 kg
<b>Mailbox</b>	22.6 in/573 mm	20.4 in/518 mm	15.2 in/386 mm	16.3 lb./7.8 kg
<b>Finisher</b>	22.6 in/573 mm	15.7 in/398 mm	15.2 in/386 mm	18.6 lb./8.8 kg
<b>Wireless Network Adapter (Wi-Fi Kit)</b>	7.4 in/188 mm	5.4 in/136 mm	2.2 in/55 mm	1.05 lb./0.1 kg

## CERTIFICATIONS

To view the latest list of certifications, go to [www.xerox.com/OfficeCertifications](http://www.xerox.com/OfficeCertifications).

## PRINT

<b>First-Print-Out Time</b>	As fast as 3.7 seconds
<b>Print Resolution</b>	Up to 1200 x 1200 dpi
<b>Page Description Languages</b>	PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe® PostScript® 3™
<b>Maximum Print Area</b>	4 mm from lead edge of paper, 2 mm from Side and Trail edges of paper

# Xerox® VersaLink® B615 Multifunction Printer

<p><b>Print Features</b></p>	<p>Application Defaults            Banner Pages Enable/Disable            Bi-directional Real-time Status            Booklet Layout            Draft Mode            Fit to New Paper Size            Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages)            Job Monitoring (Client or Local User Interface)            LAN Fax (requires Fax Kit)            N-up Page Layout (up to 16 pages per sheet)            Paper Selection by Attribute            Personal Print            Print Around Enable/Disable            Print from USB            Sample Set            Saved Job            Scaling            Secure Print            Skip Blank Pages            Special Pages (exception page programming: covers, inserts, exceptions pages)            Store and Recall Driver Settings            Stored Jobs Deletion            Two-sided Printing (as default)            Watermark (predefined and custom)            Xerox® Earth Smart Driver Settings</p>
<p><b>Print from USB</b></p>	<p>Allows walk-up printing from Type A USB port            Supports direct printing from computer via Type B USB port            Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A</p>
<p><b>Operating Systems</b></p>	<p>Windows® 7, 8, 8.1, 10            Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016            macOS® 10.11, 10.12, 10.13            Citrix®            Redhat® Enterprise Linux®            Fedora Core            IBM® AIX®            HP-UX®            Oracle® Solaris            SUSE®            SAP®</p> <p>Note: For information about supported versions for the above operating systems, please visit our Drivers &amp; Downloads page and specify your device at <a href="http://www.support.xerox.com">www.support.xerox.com</a></p>
<p><b>Fonts</b></p>	<p>PostScript fonts: 136            PCL fonts: 83</p>
<p><b>Xerox® Global Print Driver®</b></p>	<p>A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.</p>
<p><b>Xerox® Pull Print Driver</b></p>	<p>Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.</p>

Xerox® VersaLink® B615 Multifunction Printer

COPY	
<b>Document Scanner</b>	100-sheet Single-pass Duplex Automatic Document Feeder (DADF)
<b>Maximum Scan Area</b>	Platen: Up to 8.5 x 14 in./215.9 mm x 355.6 mm DADF: Up to 8.5 x 14 in./215.9 mm x 355.6 mm
<b>Simplex Copy Speed</b>	Up to 65 cpm (copies per minute) 8.5 x 11 in. black-and-white
<b>Duplex Copy Speed</b>	Up to 58.5 cpm 8.5 x 11 in. black-and-white
<b>First-Copy-Out Time</b>	As fast as 5.3 seconds
<b>Sides (input: output)</b>	1:1, 1:2, 2:2 and 2:1
<b>Quantity</b>	1 to 999
<b>Resolution (max.)</b>	Up to 600 x 600 dpi
<b>Reduction/Enlargement</b>	Variable zoom from 25% to 400% in 1% increments
<b>Concurrency</b>	Concurrent scanning and printing
<b>Copy Features</b>	Annotation (Page Numbers, Comments, Date Stamp, Bates Stamping) including font format and style options Automatic Background Suppression Book Copying with Center Erase Booklet Copying Collation Darkness Control Edge Erase Front Cover ID Card Copy Image Enhancement Image Shift Lighten/Darken N-up Original Orientation Original Size Original Type Page Layout Sample Copy Saturation Sharpness Reduce/Enlarge 25% to 400%
SCAN	
<b>Capability</b>	Black-and-white and color scanning
<b>Concurrency</b>	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs
<b>Simplex Input Speed</b>	Black-and-white: Scan up to 65 ipm (images per minute) – 8.5 x 11 in./215.9 x 279.4 mm/62 ipm A4 Color: Scan up to 55 ipm – 8.5 x 11 in./215.9 x 279.4 mm/52 ipm A4
<b>Duplex Input Speed</b>	Black-and-white: Scan up to 65 ipm (images per minute) – 8.5 x 11 in./215.9 x 279.4 mm/62 ipm A4 Color: Scan up to 55 ipm – 8.5 x 11 in./215.9 x 279.4 mm/52 ipm A4
<b>Resolution</b>	600 x 600 dpi
<b>Bit Depth</b>	24-bit color/8-bit grayscale
<b>Maximum Scan Area</b>	Platen: Up to 8.5 x 14 in./215.9 x 355.6 mm Document Feeder: Up to 8.5 x 14 in./215.9 x 355.6 mm
<b>Network Filing Protocols</b>	FTP SMTP SMB sFTP

# Xerox® VersaLink® B615 Multifunction Printer

<b>File Formats</b>	JPG TIFF (single and multi-page) XPS (single and multi-page) PDF (single and multi-page) Searchable PDF via Optical Character Recognition(OCR) Password-protected PDF Linearized PDF (set via embedded web server) and PDF/A
<b>Scan Driver Compatibility</b>	WIA TWAIN
<b>Supported Scan Destinations</b>	Scan to Home Scan to USB Scan to Email Scan to Network (FTP or Browse SMB)
<b>NETWORK SCANNING – SOFTWARE SOLUTIONS</b>	
<b>Xerox® ConnectKey® Apps (Found at the Xerox® App Gallery)</b>	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey® Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey® Apps to the ConnectKey® Technology-enabled device.
<b>FAX<sup>5</sup></b>	
<b>Fax Speed</b>	33.6 Kbps
<b>Memory</b>	4 MB
<b>Resolution</b>	Standard 200 x 100 dpi, Fine 200 x 200 dpi, Super Fine 300 x 300, 400 x 400, 600 x 600 dpi
<b>Compression</b>	MH/MR/MMR/JBIG
<b>Fax Features</b>	Walk-up Fax, LAN Fax, Direct Fax, Server Fax Enablement, Fax Forward to Email Fax dialing via Unified Address Book (up to 2,000 contacts)
<b>MOBILE SOLUTIONS AND MOBILE DEVICE APPS</b>	
<b>Apple® AirPrint®</b>	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.
<b>Mopria® Certified</b>	ConnectKey® Technology-enabled print devices are Mopria® certified. Mopria® certification ensures you can print wirelessly from your Mopria® supported (Android) smart phone, tablet and other mobile devices instantly and easily.
<b>Xerox® @printbyXerox App</b>	@printbyXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address, and release them at the MFP panel.
<b>Xerox® Print Services plug-in for Android™ (Free at Google Play™ Store)</b>	The Xerox® Print Services plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.
<b>Xerox® Easy Assist App</b>	The Xerox® Easy Assist app simplifies installation, monitoring and management of your printer or MFP right from your mobile phone. It provides easy access to self-support services and real-time monitoring of printer performance. And, Xerox® Smart Start Software takes the guess work out of setup by automating the installation of the latest software for your printer or MFP on your computer – all without IT support – allowing you to be up and running quickly.
<b>Xerox® Workplace Suite and Xerox® Workplace Cloud</b>	Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution.

SECURITY	
<b>Security Features</b>	Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol(OCSP) Cisco® Identity Services Engine (ISE)Integration Detection of External Program Falsification (XCP Plug-in) Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Email Secure Fax Secure Print Secure Scanning via SFTP Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS 1.3/SSL Trusted Platform Module (TPM)
ACCOUNTING	
XEROX® STANDARD ACCOUNTING/NETWORK ACCOUNTING (STANDARD)	
<b>Tracking</b>	Copy, Print, Fax, Scan and Email usage
<b>Accounting</b>	Xerox® Standard Accounting Tool Up to 9,999 User Accounts Up to 500 General Accounts  Network Accounting (Job Based Accounting) Up to 60,000 User IDs; Up to 60,000 Account IDs Up to 14,000 Accounting Records (transactions)
<b>Features</b>	Administrator can manage the feature via the Embedded Web Server.
ACCOUNTING OPTIONS – NETWORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)	
	<ul style="list-style-type: none"> <li>• Enhanced network accounting with up to the minute data on how the system is being used</li> <li>• Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax</li> <li>• Numerous solutions are available through Xerox Alliance Partners. For details visit <a href="http://www.xerox.com">www.xerox.com</a></li> <li>• Security enhancements include simultaneous support for HTTP/HTTPS protocols</li> <li>• Device requests account authentication from third party server enabling larger databases of users and accounts</li> <li>• Accept Authentication Login at control panel and pass to third party Networking Account</li> <li>• Interface with third party accounting terminal for accounting user interface</li> </ul>

<b>PAPER HANDLING</b>	
<b>DOCUMENT FEEDER</b>	
<b>Capacity<sup>6</sup></b>	Single-pass Duplex Automatic Document Feeder (DADF): 100 sheets
<b>Sizes</b>	Custom sizes: 5.5 x 5.5 in. to 8.5 x 14 in./140 x 140 mm to 216 x 356 mm
<b>Weights</b> One-sided: Two-sided:	16 to 32 lb. bond/60 to 128 gsm 16 to 32 lb. bond/60 to 128 gsm
<b>BYPASS TRAY</b>	
<b>Capacity<sup>6</sup></b>	150 sheets
<b>Sizes</b>	Custom sizes: 3 x 5 in. to 8.5 x 14 in./76 x 127 mm to 216 x 356 mm
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 220 gsm 16 lb. bond to 65 lb. cover/60 to 176 gsm
<b>Media Types</b>	Plain Paper Bond Punched Pre-Printed Recycled Envelopes Labels Lightweight Cardstock Cardstock Letterhead Custom 1 - 5
<b>TRAY 1</b>	
<b>Capacity<sup>6</sup></b>	550 sheets
<b>Sizes</b>	Custom sizes: 3 x 7.5 in. to 8.5 x 14 in./76.2 x 190 mm to 216 x 356 mm
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 220 gsm 16 lb. bond to 65 lb. cover/60 to 176 gsm
<b>Media Types</b>	Pre-Printed Recycled Envelopes (Tray 1 only) Labels Lightweight Cardstock Cardstock Letterhead Custom 1 - 5
<b>UP TO 4 ADDITIONAL TRAYS (OPTIONAL)</b>	
<b>Capacity<sup>6</sup></b>	550 sheets
<b>Sizes</b>	Custom sizes: 3 x 7.5 in. to 8.5 x 14 in./76.2 x 190 mm to 216 x 356 mm
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 220 gsm 16 lb. bond to 65 lb. cover/60 to 176 gsm
<b>Media Types</b>	Pre-Printed Recycled Envelopes (Tray 1 only) Labels Lightweight Cardstock Cardstock Letterhead Custom 1 - 5



# Xerox® VersaLink® B615 Multifunction Printer

<b>HIGH CAPACITY FEEDER (CAN BE COMBINED WITH 1 ADDITIONAL TRAY)</b>	
<b>Capacity<sup>6</sup></b>	2,000 sheets
<b>Sizes</b>	Standard sizes: A4 SEF, Letter SEF
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 65 lb. cover/60 to 176 gsm 16 lb. bond to 65 lb. cover/60 to 176 gsm
<b>Types</b>	Plain Paper Bond Punched Pre-Printed Recycled Lightweight Cardstock Letterhead Custom 1 - 5
<b>TOTAL PAPER CAPACITY<sup>6</sup></b>	
<b>Maximum Paper Capacity</b>	3,250 sheets
<b>PAPER OUTPUT</b>	
<b>OUTPUT TRAY</b>	
<b>Capacity<sup>6</sup></b>	400 sheets with tray full sensor (without Finisher or Mailbox)
<b>Automatic Two-sided Printing</b>	Standard
<b>FINISHER</b>	
<b>Capacity<sup>6</sup></b>	500-sheet tray, 50-sheet stapling
<b>MAILBOX</b>	
<b>Capacity<sup>6</sup></b>	Four 100-sheet bins
<b>DEVICE MANAGEMENT</b>	
<b>Network Protocols</b>	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint® FTP Most protocols not in use can be disabled
<b>Administrative Protocols</b>	DHCP, SNMP, WINS, HTTP, HTTPS, TLS 1.3, SNTP, MDNS
<b>REMOTE CONTROL PANEL</b>	
	<ul style="list-style-type: none"> <li>• Enables faster, more convenient technical support and user training</li> <li>• IT administrators and other authorized users can control the device remotely from a web page on any device</li> <li>• Remote user experience is identical to performing tasks directly at the device</li> </ul>
<b>XEROX® CENTREWARE® WEB</b>	
	<ul style="list-style-type: none"> <li>• A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>• Works with any SNMP-managed printer from any manufacturer</li> <li>• Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>

# Xerox® VersaLink® B615 Multifunction Printer

<b>EMBEDDED WEB SERVER – INTEGRATED DEVICE WEB PAGE</b>	
<b>Device Status</b>	<ul style="list-style-type: none"> <li>• Tray Status/Contents</li> <li>• Consumables Status</li> <li>• Billing/Usage</li> <li>• Quick Links</li> <li>• Online Support</li> </ul>
<b>Print Queue Viewing</b>	Job print queue management — view and delete
<b>Job Submission</b>	Print-ready files (PS, PCL, PDF, XPS, JPEG)
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device
<b>Browsers</b>	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™
<b>REMOTE SERVICES</b>	
<b>Automated Meter Readings (AMR)</b>	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
<b>Automatic Supplies Replenishment (ASR)</b>	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.
<b>WHAT COMES IN THE BOX</b>	
	VersaLink® B615 Multifunction Printer Standard Capacity Print Cartridge – Black: 10,300 print capacity <sup>7</sup> Software and Documentation CD (with User Manual, Quick Install Guide, Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power Cord Fax Cord

# Xerox® VersaLink® B615 Multifunction Printer

SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER
<b>SUPPLIES</b>		
<b>Extra-High Capacity Toner Cartridge</b>	Black: 46,700 standard pages <sup>7</sup>	106R03945
<b>High Capacity Toner Cartridge</b>	Black: 25,900 standard pages <sup>7</sup>	106R03943
<b>Standard Capacity Toner Cartridge</b>	Black: 10,300 standard pages <sup>7</sup>	106R03941
<b>Drum Cartridge</b>	Black: 60,000 pages <sup>8</sup>	101R00582
<b>ACCESSORIES/OPTIONS</b>		
<b>2,000-sheet High Capacity Feeder</b>		097S04948
<b>550-sheet Feeder</b>		097S04949
<b>Finisher</b>		097S04952
<b>4-Bin Mailbox</b>		097S04953
<b>Caster Base</b>		097S04954
<b>Stand (includes stabilizers)</b>		097S04994
<b>Wireless Network Adapter (Wi-Fi Kit)</b>		497K16750

<sup>1</sup> Declared print speed in accordance with ISO/IEC 24734.

<sup>2</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>3</sup> Recommended average throughput is not a minimum, but is intended to cover a range of volumes for different environments.

<sup>4</sup> Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

<sup>5</sup> Requires analog phone line.

<sup>6</sup> Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.

<sup>7</sup> Average standard pages. Declared Yield in accordance with ISO/IEC19752. Yield will vary based on image, area coverage and print mode.

<sup>8</sup> Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: <https://www.office.xerox.com/Latest/SUPGL-01.pdf>.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program. For more information, visit [www.xerox.com/About-Xerox/Recycling](http://www.xerox.com/About-Xerox/Recycling).

For more information, visit us at [www.xerox.com/Office](http://www.xerox.com/Office).

Configurations vary by geography.