

Xerox® VersaLink® C8000 Color Printer



The VersaLink® C8000 Color Printer is built on Xerox® ConnectKey® Technology. For more information, go to www.ConnectKey.com.

SYSTEM SPECIFICATIONS	VERSALINK® C8000DT
One-Sided Speed ¹ 8.5 x 11 in./A4 8.5 x 11 in./A4 SEF 8.5 x 14 in./216 x 356 mm 11 x 17 in./A3/297 x 420 mm/ 12 x 18 in/SRA3/320 x 450 mm	Up to 45 ppm (pages per minute) long edge feed (LEF) Up to 32 ppm Up to 26 ppm Up to 22 ppm
Two-Sided Speed ¹ 8.5 x 11 in./A4 8.5 x 11 in./A4 SEF 8.5 x 14 in./216 x 356 mm 11 x 17 in./A3/297 x 420 mm/ 12 x 18 in/SRA3/320 x 450 mm	Up to 45 ppm LEF Up to 32 ppm Up to 17 ppm Up to 15 ppm
Monthly Duty Cycle ²	Up to 205,000 pages/month
Recommended Average Monthly Print Volume ³	Up to 20,000 pages per month
Hard Drive	320 GB HDD (Optional)
Processor	1.6 GHz Dual-Core
Memory	4 GB
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n/g/b/a and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair
Controller Features	Configuration Cloning, Xerox Extensible Interface Platform®, Xerox App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan

DEVICE SPECIFICATIONS				
ELECTRICAL REQUIREMENTS				
North America		Voltage: 110-127V +/-10% Frequency: 50/60 Hz +/-3%, 12A		
Europe and Other Geographies	Voltage: 220-240V +/-10 Frequency: 50/60 Hz +/-3			
POWER CONSUMPTION				
Printing ⁴	For 110V: 2.30 kWh For 220V: 2.32 kWh			
Standby Mode ⁴	110V: 75.3 Watts or less 220V: 73.8 Watts or less			
Sleep Mode ⁴	0.67 watts or less			
OPERATING ENVIRONMENT				
Required Temperature Range(Storage)	Below 48° C, and in comp	oliance with MN2-810.13		
Required Temperature Range(Operating)	50° to 83° F (10° to 28° C Must be 28° C or below i			
Required Relative Humidity	15% to 85% Must be 62	2.5% or below at 32°C		
Sound Power Levels	Printing: 6.63 B(A) or less Standby: 3.24 B(A) or less Full System (including finisher) Printing: 7.56 B(A) Standby: 3.36 B(A)			
Sound Pressure Levels	Printing: 56.8 dB or less Standby: 15.4 dB or less Full System (including finisher) Printing: 57.1 dB Standby: 15.2 dB			
Boot Time (from Off to UI Ready)	Less than 60 seconds			
Warm-up Time (from Sleep to UI Ready)	Less than 10 seconds (without HDD) Less than 16 seconds (with HDD)			
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersaLink® C8000/DT	24.4 in./620 mm	28.5 in./723 mm	31.9 in./809.3 mm	178 lb./80.8 kg
Two Tray Module	26.3 in./668.5 mm	28.5 in./723 mm	10.3 in./261.2 mm	60.0 lb./27.2 kg
Tandem Tray Module	26.3 in./668.5 mm	28.5 in./723 mm	10.3 in./261.2 mm	74.5 lb./33.8 kg
High Capacity Feeder	15.3 in./389 mm 23.7 in./602.9 mm 15.0 in./380.01 mm 63.9 lb./29.0 kg			
Office Finisher LX	22 in./559.8 mm 21.7 in./552 mm 39.8 in./1012 mm 61.7 lb./28.0 kg			
Office Finisher with Booklet Maker attached	59.5 in./1513 mm 28.4 in./723 mm 42.3 in./1076 mm 334.2 lb./151.6 kg			
BR Booklet Maker Finisher	30.28 in./769.2 mm 28.5 in./723 mm 41.5 in./1055.1 mm 134.3 lb./60.9 kg			

DIMENSIONS AND WEIGHT (PACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersaLink® C8000/DT	32.8 in./833 mm	28.2 in./717 mm	33.4 in./852 mm	209.4 lb./95 kg
High Capacity Feeder	20.7 in./526 mm	29.8 in./756 mm	19.3 in./491 mm	74.3 lb./33.7 kg
Two Tray Module	32.7 in./830 mm	33.5 in./850 mm	15.75 in./400 mm	72.7 lb./33 kg
Tandem Tray Module	32.7 in./830 mm	33.5 in./850 mm	15.75 in./400 mm	86 lb./39 kg
Office Finishers	27.2 in./690 mm	40.2 in./1021 mm	25.7 in./654 mm	82 lb./37 kg
Booklet Maker Finisher	20 in./507 mm	30 in./761 mm	17.2 in./437 mm	31 lb./14 kg
BR Booklet Maker Finisher	30 in./764 mm	30.5 in./774 mm	47.4 in./1203 mm	169.7 lb./77 kg
Horizontal Transport for BR Booklet Maker Finisher	21 in./533 mm	23.1 in./589 mm	12.6 in./319 mm	14.3 lb./6.5 kg

CERTIFICATIONS

To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.

To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.		
PRINT		
First-Print-Out Time	As fast as 11 seconds color	
	As fast as 11 seconds black and white	
Print Resolution	Up to 1200 x 2400 dpi	
Page Description Languages	Adobe® PostScript® 3™ PCL® 5c, 6 PDF XPS TIFF JPEG HP-GL	
Color Management	Embedded spot color table, Xerox Color Corrections	
Maximum Print Area	4 mm from lead edge of paper, 2 mm from side and trail edges of paper	
Print Features	Application Defaults Banner Pages Enable/Disable Bi-directional Real-time Status Booklet Layout Color Adjustments (lightness, contrast, saturation, color balance) Color Correction Draft Mode Finishing (requires finishing) Fit to New Paper Size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable/Disable Print from USB Run Black Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming: covers, inserts, exceptions pages)	

Print from USB	Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing (as default) Watermark (predefined and custom) Xerox® Earth Smart Driver Settings Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port
Operating Systems	Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016, Server 2019 macOS® 10.11, 10.12, 10.13
	Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX® HP-UX® Oracle® Solaris SUSE® SAP® UNIX® Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com.
Fonts	PostScript fonts: 136 PCL fonts: 83
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharo® and others.
MOBILE SOLUTIONS AND MO	BILE DEVICE APPS
Apple® AirPrint®	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.
Mopria® Certified	ConnectKey® Technology-enabled print devices are Mopria® certified. Mopria certification ensures you can print wirelessly from your Mopria supported (Android™) smartphone, tablet and other mobile devices instantly and easily.
Xerox® @printbyXerox App	@printbyXerox is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® Printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address and release them at the MFP panel.
Xerox® Print Services Plug-in for Android™ (Free αt Google Play™ Store)	The Xerox® Print Service plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.

Xerox® Workplace Suite and Xerox® Workplace Cloud

Xerox® Workplace Solutions boost productivity and reduce costs with a modular print management and mobility solution. Control and manage your printer fleet while enabling mobile productivity with simplified workflows, convenience and security—for any brand printer, anywhere. Xerox® Workplace Solutions offer flexible license options to suit any size business with the ability to scale as you grow.

- Xerox® Workplace Suite: On-site, your server
- Xerox® Workplace Cloud: Simple setup, cloud administration

To learn more about the Xerox® Workplace Suite and Xerox® Workplace Cloud,

visit www.xerox.com/Mobility.

SOFTWARE SOLUTIONS

Xerox® ConnectKey® Apps (Found at the Xerox App Gallery App)

Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey® Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, Serverless ConnectKey® Apps to the device.

SECURITY

Security Features

Access Controls AES 256-bit Encryption

Audit Log

Certificate Path Validation

Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of external program falsification (XCP Plug-in)

Cisco® Identity Services Engine (ISE) Integration

Domain Filtering

FIPS 140-2

Firmware Verification Immediate Disk Overwrite*

IP Address Filtering

IPsec

Network Authentication

Port Filtering

Pre-installed Self-Signed Certificates

Role Based Permissions

Secure Print

Security Certificate Management Smart Card Enablement (CAC/PIV/.NET)

SNMPv3

Status Protocol (OCSP)

TLS/SSL

Trusted Platform Module (TPM)

*Requires HDD/Productivity Kit

ACCOUNTING

XEROX® STANDARD ACCOUNTING/NETWORK ACCOUNTING (STANDARD)

Tracking	Print usage
Accounting	Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General accounts Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 accounting records (transactions)
Features	Administrator can manage the feature via the Embedded Web Server.

ACCOUNTING OPTIONS	- NETWORK ACCOUNTING (ALLO	DWS CENTRAL SERVER TO MANAGE A	LL ACCOUNTING)	
	 Comprehensive manage Numerous solutions are Security enhancements Device requests accourd and accounts 	 Enhanced network accounting with up to the minute data on how the system is being used Comprehensive management and enterprise scale tracking and reporting of device print usage Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com Security enhancements include simultaneous support for HTTP/HTTPS protocols Device requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party Networking Account 		
PAPER HANDLING				
BYPASS TRAY				
Capacity ⁵	100 sheets			
Sizes		. to 12.6 x 19 in./88.9 x 98.4 mm to 320 x 2.6 x 52 in./88.9 x 98.4 mm to 320 x 1320		
Weights	Simplex and Duplex: 18 II	b. bond to 110 lb. cover/64 to 300 gsm		
Types	Bond Plain Paper Cardstock Custom Envelopes Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead Lightweight Cardstock	Lightweight Glossy Cardstock Pre-Printed Postcards Recycled	
TRAY 1 AND 2				
Capacity ⁵	520 sheets each			
Sizes		7 x 17 in./100 x 148 mm to 297 x 431.8 r 6 x 18 in./100 x 148 mm to 320 x 457.2 r		
Weights	Simplex and Duplex: 18 II	b. bond to 110 lb. cover/64 to 300 gsm		
Types	Bond Plain Paper Cardstock Custom Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead	Lightweight Cardstock Lightweight Glossy Cardstock Pre-Printed Recycled	
TWO TRAY MODULE				
Capacity ⁵	1,040 sheets			
Sizes	Custom sizes: 3.9 x 5.8 in.	Custom sizes: 3.9 x 5.8 in. to 12.6 x 18 in./100 x 148 mm to 320 x 457.2 mm		
Weights	Simplex and Duplex: 18 II	Simplex and Duplex: 18 lb. bond to 110 lb. cover/64 to 300 gsm		
Types	Bond Plain Paper Cardstock Custom Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead	Lightweight Cardstock Lightweight Glossy Cardstock Pre-Printed Recycled	

TANDEM TRAY MODULE				
Capacity⁵	2,000 sheets			
Sizes	8.5 x 11 in., 7.25 x 10.5 in./A4, B5			
Weights	Simplex and Duplex: 18 lb. bond to 110 lb. cover/64 to 300 gsm			
Types	Bond Plain Paper Cardstock Custom Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead	Lightweight Cardstock Lightweight Glossy Cardstock Pre-Printed Recycled	
HIGH CAPACITY FEEDER				
Capacity ⁵	2,000 sheets			
Sizes	8.5 x 11 in., 7.25 x 10.5 in./A	4, B5		
Weights	18 lb. bond to 80 lb. cover/6	4 to 216 gsm		
Types	Bond Plain Paper Cardstock Custom	Glossy Cardstock Hole Punched Letterhead Lightweight Cardstock	Lightweight Glossy Cardstock Recycled	
ENVELOPE TRAY – REPLACES TRA	Y 1 (OPTIONAL)			
Capacity ⁵	Up to 50 envelopes			
Sizes	#10 commercial, Monarch, DL, C4, C5, C6 Custom sizes: 3.5 x 3.85 in. to 9.5 x 13.1 in./90 x 98 mm to 241 x 332 mm			
TOTAL CAPACITY				
VersaLink® C8000/DT Capacity ⁵	1,140 sheets			
Maximum Capacity ⁵	5,140 sheets			
FINISHING				
OUTPUT TRAYS				
Dual Offset Catch Tray (Standard when finishers are not attached)	500 sheets (without center tray) 2x 250 sheets (with center tray when offset is off) 2x 125 sheets (with center tray when offset is on)			
OFFICE FINISHERS (OPTIONAL)				
Capacity⁵	Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in./A4) (dual stapling only with optional booklet maker) Offset available for collated sets of standard size paper (8.5 x 11 in./A4 to 11 x 17 in./A3)			
Sizes Office Finisher LX Office Finisher Weights	8.3 x 7.2 in. to 11.7 x 17 in./210 x 182 mm to 297 x 432 mm 5.8 to 11.7 in x 5.8 to 17 in/148.0 to 297.0 mm x 148.0 to 432.0 mm			
Office Finisher LX Office Finisher	16 lb. bond to 80 lb. cover / 60 to 220 gsm 16 lb. bond to 95 lb. cover / 60 to 256 gsm			
Multi-position Stapling	50 sheets of 24 lb. bond/90 gsm			
Hole Punch (Optional) North America: Europe and Other Geographies:	Office Finisher LX: up to 65lb. cover (200 gsm)/Office Finisher: up to 80 lb. cover (220 gsm) 2/3 hole punch 2/4 hole punch			
BOOKLET MAKER FOR OFFICE FIL	NISHERS (SCORE/CREASE, SA	ADDLE-STITCH STAPLE) (OPTIONA	L)	
Capacity⁵	40 booklets (2 to 15 sheets per booklet – 20 lb./80 gsm or less)			
Sizes	Letter – 8.5 x 11 in./A4 SEF L	Letter – 8.5 x 11 in./A4 SEF Legal – 8.5 x 14 in./B4 SEF Ledger – 11 x 17 in./A3 SEF		

Saddle-stitch Stapling	2 to 15 sheets/8-60 page booklet 18 lb. bond to 24 lb. bond/60 to 90 gsm		
Score/Crease	1 to 15 sheets/unstapled/60 to 105 gsm only		
OPTIONAL BR BOOKLET MAKER FINISHER (REQUIRES HORIZONTAL TRANSPORT KIT)			
Capacity ⁵	Offsetting Top Tray: 500 sheets of 8.5 x 11 in./A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in./A1 x 17 in./A4/A3 unstapled or 200 stapled sets of 8.5 x 11 in./A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of 11 x 17 in./A3		
Sizes	4 x 6 in. to 11 x 17 in./A6 to A3 for stacking 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling		
Weights	16 lb. bond to 110 lb. cover/60 to 300 gsm (coated and uncoated)		
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb./90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported		
Hole Punch North America Europe	2/3 hole punch 2/4 hole punch 4 hole "Swedish" punch (optional)		
Booklet Maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 supported		
DEVICE MANAGEMENT			
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint™ Most protocols not in use can be disabled		
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS		
REMOTE CONTROL PANEL			
	 Enables faster, more convenient technical support and user training IT administrators and other authorized users can control the device remotely from a web page on any device Remote user experience is identical to performing tasks directly at the device 		
XEROX® CENTREWARE® WEB			
	 A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system Works with any SNMP-managed printer from any manufacturer Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management 		
XEROX® EMBEDDED WEB SER	XEROX® EMBEDDED WEB SERVER – INTEGRATED DEVICE WEB PAGE		
Device Status	 Tray status/Contents Consumables Status Billing/Usage Quick Links Online Support 		
Print Queue Viewing	Job print queue management—view and delete		
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG, TXT, PRN, TIF)		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device		

Browsers	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™		
REMOTE SERVICES			
Xerox® Automated Meter Reads (AMR)	Automates the process of collecting and submitting meter red Device usage. Eliminates the need for time-consuming end-us reads are submitted to Xerox on time.		
Xerox® Automatic Supplies Replenishment (ASR)	Automatically orders supplies for output devices from Xerox be need to manually manage supplies inventory.	ased on actual usage, eliminating the	
WHAT'S IN THE BOX			
	 VersaLink® C8000 Color Printer Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow: 8,000 print capacity)⁶, Black:12,000 print capacity⁶ Drum Cartridge – One of each (Cyan, Magenta, Yellow, & Black: 190,000 print capacity)⁷ Quick Use Guide Install Guide Software and Documentation CD (with Drivers, Warranty Statement and Safety Regulatory Recycle Disposal Guide) Power Cord 		
SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER	
SUPPLIES		•	
Standard Capacity TonerCartridges	Cyan: 7,600 standard pages ⁶ Magenta: 7,600 standard pages ⁶ Yellow: 7,600 standard pages ⁶ Black: 12,600 standard pages ⁶	106R04042 106R04043 106R04044 106R04045	
High Capacity Toner Cartridges	Cyan: 16,500 standard pages ⁶ Magenta: 16,500 standard pages ⁶ Yellow: 16,500 standard pages ⁶ Black: 20,900 standard pages ⁶	106R04054 106R04055 106R04056 106R04057	
Drum Cartridge	Cyan: 190,000 standard pages ⁷ Magenta: 190,000 standard pages ⁷ Yellow: 190,000 standard pages ⁷ Black: 190,000 standard pages ⁷	101R00602	
Waste Cartridge	47,000 standard pages ⁷	108R01504	
IBT Cleaner	160,000 standard pages ⁷ 104R00256		
Transfer Roller	200,000 standard pages ⁷	116R00015	
Office Finisher Booklet Maker Cartridge (8 cartridges per container)	16,000 staples (2,000 each cartridge)	008R12897	
Staple Refills for Office Finisher(3 refills per container)	15,000 staples (5,000 each refill)	008R12941	
Staple Cartridges for BR Finisher and Office Finisher (1 cartridge per carton)	5,000 staples 008R12964 (5,000 each cartridge)		
Staple Cartridges for BR Booklet Maker (1 cartridge per carton)	5,000 staples 008R13177 (5,000 each cartridge)		

Xerox® VersaLink® C8000 Color Printer

ACCESSORIES/OPTIONS	
Two Tray Module	097S04969
Tandem Tray Module	097S04970
High Capacity Feeder	097S04845
Envelope Tray (Replaces Tray 1)	497K17880
Office Finisher LX (Includes Gap Filler)	097S04848 497K17370
Office Finisher	097S05019
2/3 Hole Punch for Office Finisher LX (available Western Hemisphere)	497K03860
2/3 Hole Punch for Office Finisher (available Western Hemisphere)	497K20600
2/4 Hole Punch for Office Finisher LX (available Western Hemisphere)	497K03870
2/4 Hole Punch for Office Finisher (available in Western Hemisphere)	497K20610
Booklet Maker for Office Finisher LX	497K03852
Booklet Maker for Office Finisher	497K20590
BR Booklet Maker Finisher with 2/3 Hole Punch (comes with Horizontal Transport)	497K21000
BR Booklet Maker Finisher with 2/4 Hole Punch	097S04982
Swedish 4 Hole Punch for BR Finisher	497K14370
320 GB HDD	097S04971
Wireless Network Adapter Kit	497K16750
Internal Card Reader/RFID Kit	497K18120 (Western Hemisphere) 497K18140 (Eastern Hemisphere)

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program. For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.

Configurations vary by geography.



¹ Declared print speed in accordance with ISO/IEC 24734.
2 Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
3 Recommended average throughput is not a minimum, but is intended to cover a range of volumes for different environments.
4 Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.
5 Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.
6 Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.
7 Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: http://www.office.xerox.com/latest/SUPGL-01.pdf.